

# M-SERIES M100



## MAGNETRON MODULATOR UP TO 3.1 MW

**ScandiNova's M100** is a stand-alone pulse Modulator in a very compact enclosure. The Modulator is optimized for a wide range of different magnetrons with an RF peak power ranging from 1.0 MW to 3.1 MW. The M100 is also available as an integrated and/or dual version (see M100-i, M100D, and M100D-i).

All interlocks and essential diagnostics are fully integrated, and ScandiNova's modern control system offers a user-friendly interface. The pulse length, amplitude and repetition rate can all be changed.

The M100 can be delivered as a pure high-power pulse modulator or as part of an RF Unit including magnetron and related components. Different levels of service and support programmes are available.

COMPACT

UP TO 3.1 MW RF PEAK POWER

FULLY COMPUTERIZED

MINIMIZED CONSUMABLES

## THE M-SERIES

**ScandiNova's M-series** contains a range of magnetron pulse modulators with high reliability and performance, a compact design and low energy consumption.

Our magnetron pulse modulators require about one third of the space of alternative solutions yet still offer around 30% higher efficiency, two operating advantages that especially appeal to cancer treatment providers.


Their high reliability and performance also attract many industry applications.

SPECIFICATIONS	UNIT	VALUE	NOTES
Magnetron RF peak power	MW	1-3.1	Depends on choice of magnetron
Magnetron RF average power	kW	2.8	Maximum, depends on choice of magnetron
Modulator peak power	MW	6.2	Maximum
Modulator average power	kW	8	Maximum
Pulse voltage	kV	30-52	
Pulse current	A	30-120	
RF pulse length, top	µs	0.5-5	Depends on max average power
Pulse repetition rate	Hz	0-500	Depends on max average power
Modulator Voltage Stability, RMS	%	0.4	Verified on resistive load (see options)
Water cooling	l/min	8	18-40 °C, non-condensing

INTERFACE	CONNECTOR	DEFAULT	OPTION
Mains power, three-phase	Terminal block (4-wire)	400±10 % VAC, 50/60 Hz	208/380/480 VAC
Mains power, single-phase	C20	230±10 % VAC, 50/60 Hz	115 VAC
Control interface	RJ45	Modbus TCP	
Water cooling interface	12 mm	Legris Push-in	Swagelock
Trig input	BNC	Electrical	Optical
Diagnostics	BNC	Pulse voltage & current signals	

SIZE AND WEIGHT	UNIT	VALUE
Weight (incl. oil)	kg	140

For more information, visit [www.scandinovsystems.com/M100](http://www.scandinovsystems.com/M100)



Contact ScandiNova for any requirements not covered by this specification.

Information contained in this document is subject to change without notice.

#### The Standard Modulator Includes

- Filament power supply
- Control system
- Control via Modbus TCP
- Pulse sensors
- HV pulse cable
- Internal trig generator
- Factory acceptance test certificate
- Manuals

#### Options

- Pulse/RF diagnostics
- Enhanced PRF range (1000-2000 Hz)
- Enhanced stability (down to 0.1 %)
- Digitizer
- Gunport
- Peaking components

#### Additional System Components

- Circulator & RF loads
- Directional coupler
- Magnet power supply
- Waveguide windows
- Magnetron

#### Services

- Training in handling, operation and maintenance
- Shipping
- Installation and start-up
- Service contract

#### Typical Magnetron Loads

<b>BVERI</b>	<b>GLVAC</b>
VE2110	VE2110A
	VE2098

#### Nisshinbo

M1603	<b>GLM</b>
M1466	GLM5193
MX7640	GLM5810
M1466N	GLM6090

#### CPI

<b>E2V</b>	VMC3109
------------	---------

MG2025	VMC3136
--------	---------

MG5125	
--------	--

MG5193	
--------	--

MG6090	
--------	--

MG6493	
--------	--

MG7095	
--------	--

COMPANY WITH  
MANAGEMENT SYSTEM  
CERTIFIED BY DNV  
ISO 9001 • ISO 14001

#### HEADQUARTERS

ScandiNova Systems AB  
Typsnittsgatan 15  
SE-754 54 Uppsala, Sweden

#### CONTACT

Tel: +46 (0)18 480 59 00  
E-mail: [info@scandinovsystems.com](mailto:info@scandinovsystems.com)  
[www.scandinovsystems.com](http://www.scandinovsystems.com)

**ScandiNova**  
Excellence in pulsed power